

规格/TECHNICAL SPECIFICATIONS

型号/MODEL NUMBER:

I LENS796-R17371-15-12H1-NH-S

透镜尺寸/LENS DIMENSIONS:



173.0*71.4*10.1MM

定位方式/FASTENING:

锁螺丝、定位柱/Screw or Pin

是否符合ROHS/ROHS COMPLIANT:


是/YES




说明/CHARACTERISTIC:

1. 透镜有多种不同的配光角度。
The lens have multiple types beam angles.
2. 一体化透镜配硅胶圈。
Silicone gasket available for waterproof.
3. 兼容多种灯珠。
Compatible with various lamp beads.
4. 适用于球场灯、投光灯。
Suitable for Stadium light, flood light.
5. I LENS229升级, 光效更好, 光斑更漂亮, 兼容性更好。
I LENS229 upgrade, better light effect, more beautiful spot and better compatibility.


LED:CREE XPE2
 角度/FWHM:13.5°
 光效/Efficiency:82%
 峰值强度/Peakintensity:6.5CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:CREE XPG2
 角度/FWHM:15°
 光效/Efficiency:81%
 峰值强度/Peakintensity:5.5CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:CREE XML2
 角度/FWHM:19.4°
 光效/Efficiency:81%
 峰值强度/Peakintensity:3.8CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:CREE XPL2
 角度/FWHM:20.3°
 光效/Efficiency:80%
 峰值强度/Peakintensity:3.1CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:CREE XD16
 角度/FWHM:15.4°
 光效/Efficiency:83%
 峰值强度/Peakintensity:6.1CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:LUXEON 3030 2D
 角度/FWHM:16.5°
 光效/Efficiency:84%
 峰值强度/Peakintensity:5.4CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:LUXEON 5050
 角度/FWHM:26.5°
 光效/Efficiency:83%
 峰值强度/Peakintensity:2.6CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:SAMSUNG LH351B
 角度/FWHM:17.2°
 光效/Efficiency:81%
 峰值强度/Peakintensity:4.3CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:CREE XPE2
 角度/FWHM:13°
 光效/Efficiency:91%
 峰值强度/Peakintensity:6.8CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:CREE XPG2
 角度/FWHM:14.9°
 光效/Efficiency:91%
 峰值强度/Peakintensity:5.7CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:CREE XML2
 角度/FWHM:19°
 光效/Efficiency:91%
 峰值强度/Peakintensity:3.9CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:CREE XPL2
 角度/FWHM:20.6°
 光效/Efficiency:90%
 峰值强度/Peakintensity:3.2CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:CREE XD16
 角度/FWHM:15.8°
 光效/Efficiency:92%
 峰值强度/Peakintensity:6.0CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:LUXEON 3030 2D
 角度/FWHM:17.6°
 光效/Efficiency:93%
 峰值强度/Peakintensity:5.0CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::




LED:LUXEON 5050
 角度/FWHM:27.5°
 光效/Efficiency:92%
 峰值强度/Peakintensity:2.5CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::



LED:SAMSUNG LH351B
 角度/FWHM:17.0°
 光效/Efficiency:91%
 峰值强度/Peakintensity:4.4CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components::







注意/NOTE:

1. 镜片表面应光滑无划痕、气泡、凹痕和黑点。
The surface of the lens should be smooth without scratches, bubbles, dents and black spots.


GENERAL TOL ERANCES ISO2768-M (UNLESS STATED) 一般公差ISO 2768-M (除非另有说明)	MATERIL 材质	PMMA or PC	DRAWING TITLE 绘图标题	ILENS796-R17371-15-12H1-NH-S
LINEAR/线性	0~5±0.05		5~10±0.1	10~30±0.15
ANGULAR/角度	0°~10°±1°		10°~50°±0.5°	50°~120°±0.3°

产品包装/PRODUCTS PACKAGING

型号/Part No.	数量/QTY
ILENS796-R17371-15-12H1-NH-S	250pcs
吸塑/Blister-380*380*20	25pcs
外盒/Cardboard box(M)	1pcs



示意图/The schematic diagram :



备注：防水硅胶圈是单独包装的
PS: The waterproof rubber ring is packaged separately.