




规格/TECHNICAL SPECIFICATIONS


型号/MODEL NUMBER:	I LENS796-R17371-25-12H1-NH-S
透镜尺寸/LENS DIMENSIONS:	173.0*71.4*10.1MM
定位方式/FASTENING:	锁螺丝、定位柱/Screw or Pin
是否符合ROHS/ROHS COMPLIANT:	是/YES




说明/CHARACTERISTIC:

1. 透镜有多种不同的配光角度。
The lens have multiple types beam angles.
2. 一体化透镜配硅胶圈。
Silicone gasket available for waterproof.
3. 兼容多种灯珠。
Compatible with various lamp beads.
4. 适用于球场灯、投光灯。
Suitable for Stadium light, flood light.
5. I LENS229升级, 光效更好, 光斑更漂亮, 兼容性更好。
I LENS229 upgrade, better light effect, more beautiful spot and better compatibility.


LED:CREE XPG2
 角度/FWHM:32°
 光效/Efficiency:91%
 峰值强度/Peakintensity:2.5CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:




LED:CREE XML2
 角度/FWHM:33°
 光效/Efficiency:91%
 峰值强度/Peakintensity:2.3CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:




LED:CREE XPL2
 角度/FWHM:35°
 光效/Efficiency:89%
 峰值强度/Peakintensity:2.0CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:




LED:CREE XD16
 角度/FWHM:27.5°
 光效/Efficiency:91%
 峰值强度/Peakintensity:3.3CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:




LED:LUXEON 3030 2D
 角度/FWHM:27°
 光效/Efficiency:91%
 峰值强度/Peakintensity:3.6CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:




LED:LUXEON 5050
 角度/FWHM:33°
 光效/Efficiency:90%
 峰值强度/Peakintensity:2.3CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:




LED:SAMSUNG LH231B
 角度/FWHM:29°
 光效/Efficiency:91%
 峰值强度/Peakintensity:3.2CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:




LED:SAMSUNG LH351B
 角度/FWHM:33°
 光效/Efficiency:91%
 峰值强度/Peakintensity:2.4CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:




LED:CREE XPG2
 角度/FWHM:29°
 光效/Efficiency:96%
 峰值强度/Peakintensity:3.0CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:




LED:CREE XML2
 角度/FWHM:30°
 光效/Efficiency:96%
 峰值强度/Peakintensity:2.7CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:




LED:CREE XPL2
 角度/FWHM:32°
 光效/Efficiency:95%
 峰值强度/Peakintensity:2.3CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:




LED:CREE XD16
 角度/FWHM:24°
 光效/Efficiency:96%
 峰值强度/Peakintensity:4.1CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:




LED:LUXEON 3030 2D
 角度/FWHM:24°
 光效/Efficiency:96%
 峰值强度/Peakintensity:4.3CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:




LED:LUXEON 5050
 角度/FWHM:31.5°
 光效/Efficiency:96%
 峰值强度/Peakintensity:3.5CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:









LED:SAMSUNG LH231B
 角度/FWHM:26°
 光效/Efficiency:96%
 峰值强度/Peakintensity:3.7CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:



LED:SAMSUNG LH351B
 角度/FWHM:30°
 光效/Efficiency:96%
 峰值强度/Peakintensity:2.7CD/LM
 光学面数量/LED/each optic:12
 灯光颜色/Light colour: 白色/White
 所需组件/Required components:







注意/NOTE:
1. 镜片表面应光滑无划痕、气泡、凹痕和黑点。
The surface of the lens should be smooth without scratches, bubbles, dents and black spots.


GENERAL TOL ERANCES ISO2768-M (UNLESS STATED) 一般公差ISO 2768-M(除非另有说明)	MATERIL 材质	PMMA or PC	DRAWING TITLE 绘图标题	ILENS796-R17371-25-12H1-NH-S	
LINEAR/线性	0~5±0.05		5~10±0.1	10~30±0.15	
ANGULAR/角度	0°~10°±1°		10°~50°±0.5°	50°~120°±0.3°	

产品包装/PRODUCTS PACKAGING

型号/Part No.	数量/QTY
ILENS796-R17371-25-12H1-NH-S	250pcs
吸塑/Blister-380*380*20	25pcs
外盒/Cardboard box(M)	1pcs



示意图/The schematic diagram :



备注：防水硅胶圈是单独包装的
PS: The waterproof rubber ring is packaged separately.